


- 1. Take one base frame, one set of wheels
- 2. Use screws and nuts to fix wheels on the base frame




- 1. Take one set base frame unit, one set lower shelf frame unit
- 2. Use screws and nuts to fix lower shelf frame unit on base frame unit
- 3. Take two link bars, installed on the top of cart frame


- LOWER SHELF FRAME

 SCREW

 SCREW
 - 1. Take two lower shelf frames and two support bars
 - 2. Use screws and nuts to fix support bars on the lower shelf frame



- 1. Take two upper shelf frames, two support bars, two link bars
- 2. Use screws and nuts to fix support bar on upper shelf frame
- 3. Use screws and nuts to fix link bar on upper shelf frame



- 1. Take one set upper frame unit, one set lower shelf frame unit, one set base frame unit
- 2. Use screws and nut to fix them together
- 3. Fasten all screws to finish assembly

Check that all bolts are tight before use.

NOTE: This model cart is designed for use with a specific diameter of stanchion. Please ensure the model you have is compatible with your stanchions. If stanchions are not a tight fit, they may slide out of the racks causing risk of injury.

WARNING: DO NOT USE WITHOUT STRAPPING DOWN THE TOP LAYER OF STANCHIONS. LOAD FROM THE BOTTOM UP